

# Classics Rigid 30/55/70

## Datasheet

	Norm	iD Click Ultimate 70	iD Click Ultimate 55	iD Click Ultimate 30 (2023)
<b>Classification</b>				
Product type	EN ISO 10582	Heterogeneous poly(vinyl chloride) floor coverings (ISO 10582)		
Domestic classification	EN ISO 10874	23 Heavy		
Commercial classification	EN ISO 10874	34 Very Heavy	33 Heavy	31 Moderate
<b>Characteristics</b>				
Total thickness	EN ISO 24346	6.50 mm		5.50 mm
Wear layer thickness	EN ISO 24340	0.70 mm	0.55 mm	0.30 mm
Total weight	EN ISO 23997	10600 g/m <sup>2</sup>	10700 g/m <sup>2</sup>	8900 g/m <sup>2</sup>
Binder content	EN ISO 10582	Type I		
Surface treatment		TEKTANIUM®		
Bevelled edges		4 sides		
Installation method		Click		
<b>Performance for CE Marking</b>				
Declaration of Performance	EN 14041	0197-0058-DoP-2022-11	0197-0057-DoP-2022-11	0197-0056-DoP-2022-11
<b>Technical Performance</b>				
Dimensional stability	EN ISO 23999	Average measured value : ≤ 0.10 % ≤ 0,15 %		
Curl resistance to heat	EN ISO 23999	≤ 1mm		
Reaction to fire	EN 13501-1	Bfl-s1		
Residual indentation	EN ISO 24343-1	Average measured value: 0,02 mm ≤ 0.10 mm		
Castor chair effect	EN ISO 4918	No damage		
Impact sound reduction - ΔLw	EN ISO 717-2	19 dB		
Drum sound class	NF S31-074	C		
Thermal resistance (m <sup>2</sup> K/W)	EN ISO 10456	0,07 m <sup>2</sup> •K/W		0,06 m <sup>2</sup> •K/W
Colour fastness to light	EN ISO 105-B02	≥ 6		
Chemical resistance	EN ISO 26987	Good resistance		
Slip resistance	DIN 51130	R10		
Slip resistance	EN 13893	Class DS (μ ≥ 0.30)		
Peeling Resistance	EN ISO 24345	≥ 50N/50mm		
Underfloor heating		Suitable (subfloor temperature maximum 27°C)		
<b>Sustainability, Environment &amp; Indoor Air Quality</b>				
Recyclable		Yes - offcuts and post-use through ReStart® (ISO 14021)		
Total recycled content	ISO 14021	20 %		
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		12.26 kg CO <sub>2</sub> e /m <sup>2</sup>		10.60 kg CO <sub>2</sub> e /m <sup>2</sup>
Total Carbon Footprint (EPD Modules A-D, incl. recycling scenario)		6.41 kg CO <sub>2</sub> e /m <sup>2</sup>		9.02 kg CO <sub>2</sub> e /m <sup>2</sup>
Phthalate free		Yes		
TVOC emissions after 28 days	EN 16516	Platinum (≤ 10 μg/m <sup>3</sup> )		
Formaldehyde emission		E1		
Material Health Statement		Yes		
French emissions label		A+		
<b>Dimensions and designs</b>				
Plank		Plank 1200 x 200,5mm - 5 Planks=1.203 m <sup>2</sup> /box - 60 boxes/pallet Plank 1500 x 243mm - 3 Planks=1.094 m <sup>2</sup> /box - 69 boxes/pallet	Plank 1500 x 243mm - 3 Planks=1.094 m <sup>2</sup> /box - 66 boxes/pallet Plank 1200 x 200,5mm - 5 Planks=1.203 m <sup>2</sup> /box - 60 boxes/pallet	Plank 1200 x 200,5mm - 7 Planks=1.684 m <sup>2</sup> /box - 52 boxes/pallet
Tile		Tile 640 x 320mm - 7 Tiles=1.434 m <sup>2</sup> /box - 52 boxes/pallet Tile 960 x 480mm - 3 Tiles=1.382 m <sup>2</sup> /box - 54 boxes/pallet	Tile 960 x 480mm - 3 Tiles=1.382 m <sup>2</sup> /box - 54 boxes/pallet Tile 640 x 320mm - 7 Tiles=1.434 m <sup>2</sup> /box - 52 boxes/pallet	Tile 640 x 320mm - 9 Tiles=1.843 m <sup>2</sup> /box - 48 boxes/pallet
Number of designs available		24	24	17



The above information is subject to modification for the benefit of further improvement (30/07/2024). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com> Tarkett's instructions regarding installation, cleaning and maintenance should be observed.

Please contact Tarkett at the address shown for the instructions.